

# Package ‘ManyTests’

January 20, 2025

**Type** Package

**Title** Multiple Testing Procedures of Cox (2011) and Wong and Cox (2007)

**Version** 1.2

**Date** 2016-10-30

**Author** Christiana Kartsonaki

**Maintainer** Christiana Kartsonaki <christiana.kartsonaki@gmail.com>

**Description** Performs the multiple testing procedures of Cox (2011) <[doi:10.51170/CERN-2011-006](https://doi.org/10.51170/CERN-2011-006)> and Wong and Cox (2007) <[doi:10.1080/02664760701240014](https://doi.org/10.1080/02664760701240014)>.

**License** GPL-2

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2016-10-31 16:53:46

## Contents

ManyTests-package . . . . .	2
FDR . . . . .	2
local_slope . . . . .	3
ordered_values . . . . .	4
plot_pvalues . . . . .	5
t_0 . . . . .	6

## Index

7

ManyTests-package      *Multiple Testing Procedures of Cox (2011) and Wong and Cox (2007)*

### Description

Performs the multiple testing procedures of Cox (2011) and Wong and Cox (2007).

### Details

Package:	ManyTests
Type:	Package
Version:	1.1
Date:	2016-10-30
License:	GPL-2

### Author(s)

Christiana Kartsonaki

Maintainer: Christiana Kartsonaki <christiana.kartsonaki@gmail.com>

### References

- Cox, D. R. (2011). Discovery: a statistical perspective. *Phystat Conference CERN*. <doi:10.5170/CERN-2011-006>
- Cox, D. R. and Wong, M. Y. (2004). A simple procedure for the selection of significant effects. *Journal of the Royal Statistical Society B* **66** (2), 395–400. <doi:10.1111/j.1369-7412.2004.05695.x>
- Wong, M. Y. and Cox, D. R. (2007). On the screening of large numbers of significance tests. *Journal of Applied Statistics* **34** (7), 779–783. <doi:10.1080/02664760701240014>

FDR

*False Discovery Rate corresponding to t\_0*

### Description

Calculates the FDR which corresponds to a given cut-off  $t_0$  according to the procedure of Wong and Cox (2007).

### Usage

```
FDR(test_statistics, t_0)
```

**Arguments**

test_statistics	A vector of values of test statistics.
t_0	A cut-off value.

**Value**

The FDR which corresponds to a given cut-off t\_0.

**Author(s)**

Christiana Kartsonaki

**References**

- Cox, D. R. and Wong, M. Y. (2004). A simple procedure for the selection of significant effects. *Journal of the Royal Statistical Society B* **66** (2), 395–400. <doi:10.1111/j.1369-7412.2004.05695.x>
- Wong, M. Y. and Cox, D. R. (2007). On the screening of large numbers of significance tests. *Journal of Applied Statistics* **34** (7), 779–783. <doi:10.1080/02664760701240014>

**See Also**

[t\\_0](#)

**Examples**

```
x <- c(rnorm(100, 2, 2), rnorm(50, 0, 2))
FDR(x, t_0(x))
```

---

local\_slope

*Calculate and test the local slope of the plot at large values*

---

**Description**

Calculates the effective slope of the plot at large values and tests the deviation of the largest value from that line (Cox, 2011).

**Usage**

```
local_slope(p, k)
```

**Arguments**

p	Vector of <i>p</i> -values.
k	Number of 'top' k values.

**Value**

- `local_slope` The estimated local slope of the plot at large values.  
`test_statistic` The value of the test statistic.  
`Fvalue` The upper 5% value of the F distribution with 2 and 2k degrees of freedom, which is the distribution of the test statistic under the null hypothesis.  
`pvalue` The *p*-value of the test.

**Author(s)**

Christiana Kartsonaki

**References**

- Cox, D. R. (2011). Discovery: a statistical perspective. *Phystat Conference CERN*. <doi:10.5170/CERN-2011-006>

**See Also**

[plot\\_pvalues](#)

**Examples**

```
# generate a vector of p values
p <- runif(100, 0, 1)

local_slope(p, 10)
```

`ordered_values`

*Calculate the expected values of the Renyi decomposition*

**Description**

Calculates the expected values of the Renyi decomposition.

**Usage**

`ordered_values(n)`

**Arguments**

- `n` Number of values.

**Value**

A vector of length `n`.

**Author(s)**

Christiana Kartsonaki

**References**

Cox, D. R. (2011). Discovery: a statistical perspective. *Phystat Conference CERN*. <doi:10.5170/CERN-2011-006>

**Examples**

```
ordered_values(10)
```

---

`plot_pvalues`

*Plot transformed p-values against the expected values of the Renyi decomposition*

---

**Description**

Plots  $-\log(p)$  against the expected values of the Renyi decomposition (Cox, 2011).

**Usage**

```
plot_pvalues(p)
```

**Arguments**

`p` A vector of  $p$ -values.

**Author(s)**

Christiana Kartsonaki

**References**

Cox, D. R. (2011). Discovery: a statistical perspective. *Phystat Conference CERN*. <doi:10.5170/CERN-2011-006>

**See Also**

[local\\_slope](#)

**Examples**

```
# generate a vector of p-values
p <- runif(100, 0, 1)

plot_pvalues(p)
```

*t\_0**Cut-off level corresponding to unit Bayes factor***Description**

Calculates the cut-off level corresponding to unit Bayes factor according to the procedure of Wong and Cox (2007).

**Usage**

```
t_0(test_statistics)
```

**Arguments**

<i>test_statistics</i>	A vector of values of test statistics.
------------------------	--

**Value**

Cut-off level corresponding to unit Bayes factor.

**Author(s)**

Christiana Kartsonaki

**References**

- Cox, D. R. and Wong, M. Y. (2004). A simple procedure for the selection of significant effects. *Journal of the Royal Statistical Society B* **66** (2), 395–400. <doi:10.1111/j.1369-7412.2004.05695.x>
- Wong, M. Y. and Cox, D. R. (2007). On the screening of large numbers of significance tests. *Journal of Applied Statistics* **34** (7), 779–783. <doi:10.1080/02664760701240014>

**See Also**

[FDR](#)

**Examples**

```
x <- c(rnorm(100, 2, 2), rnorm(50, 0, 2))
t_0(x)
```

# Index

FDR, [2](#), [6](#)

local\_slope, [3](#), [5](#)

ManyTests (ManyTests-package), [2](#)

ManyTests-package, [2](#)

ordered\_values, [4](#)

plot\_pvalues, [4](#), [5](#)

t\_0, [3](#), [6](#)