

Package ‘PRMethods’

February 14, 2025

Type Package

Title D-Hondt, Sainte-Lague, and Modified Sainte-Lague Methods for Seat Allocation

Version 0.1.0

Maintainer Pau Bello Pérez <paubelloperez@gmail.com>

Description Calculates seat allocation using the D-Hondt method, Sainte-Lague method, and Modified Sainte-Lague method, all commonly used in proportional representation electoral systems. For more information on these methods, see Michael Gallagher (1991)<[doi:10.1016/0261-3794\(91\)90004-C](https://doi.org/10.1016/0261-3794(91)90004-C)>.

License MIT + file LICENSE

Encoding UTF-8

RoxxygenNote 7.3.2

VignetteBuilder knitr

NeedsCompilation no

Author Pau Bello Pérez [aut, cre]

Repository CRAN

Date/Publication 2025-02-14 14:30:10 UTC

Contents

dhondt	2
saintelague	2
saintelaguemod	3

Index

4

dhondt

*DHondt method for seats allocation.***Description**

DHondt method for seats allocation.

Usage

```
dhondt(votes, seats, threshold = 0, verbose = TRUE)
```

Arguments

<code>votes</code>	Un vector con los votos de cada partido.
<code>seats</code>	Total de seats a repartir.
<code>threshold</code>	Umbral electoral
<code>verbose</code>	Muestra los resultados en la consola

Value

Un vector con los seats asignados a cada partido.

Examples

```
votes <- c(A = 100000, B = 75000, C = 50000, D = 25000)
dhondt(votes, 10)
```

saintelague

*Sainte-Lague method for seats allocation.***Description**

Sainte-Lague method for seats allocation.

Usage

```
saintelague(votes, seats, threshold = 0, verbose = TRUE)
```

Arguments

<code>votes</code>	Un vector con los votos de cada partido.
<code>seats</code>	Total de seats a repartir.
<code>threshold</code>	Umbral electoral
<code>verbose</code>	Muestra los resultados en la consola

Value

Un vector con los seats asignados a cada partido.

Examples

```
votes <- c(A = 100000, B = 75000, C = 50000, D = 25000)
saintelague(votes, 10)
```

saintelaguemod

Modified Sainte-Lague method for seats allocation.

Description

Modified Sainte-Lague method for seats allocation.

Usage

```
saintelaguemod(votes, seats, threshold = 0, div = 1.4, verbose = TRUE)
```

Arguments

votes	Un vector con los votos de cada partido.
seats	Total de seats a repartir.
threshold	Umbral electoral
div	Divisor modificado en Modified Sainte-Lague
verbose	Muestra los resultados en la consola

Value

Un vector con los seats asignados a cada partido.

Examples

```
votes <- c(A = 100000, B = 75000, C = 50000, D = 25000)
saintelaguemod(votes, 10)
```

Index

`dhondt`, 2

`saintelague`, 2

`saintelaguemod`, 3