

Package ‘QRISK3’

January 20, 2025

Title 10-Year Cardiovascular Disease Risk Calculator (QRISK3 2017)

Version 0.6.0

Author Yan Li <bluefatterplaydota@gmail.com> [aut, cre, trl],
Matthew Sperrin [aut, ctb],
ClinRisk Ltd. [cph],
Tjeerd Pieter van Staa [aut, ths]

Maintainer Yan Li <bluefatterplaydota@gmail.com>

Description This function aims to calculate risk of developing cardiovascular disease of individual patients in next 10 years. This unofficial package was based on published open-sourced free risk prediction algorithm QRISK3-2017 <<https://qrisk.org/src.php>>.

Copyright file inst/COPYRIGHTS

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

NeedsCompilation no

Repository CRAN

Date/Publication 2023-07-20 05:10:02 UTC

Contents

QRISK3_2017	2
QRISK3_2017_test	4
QRISK3_2019_test	5

Index

6

Description

This function allows you to calculate 10-year individual CVD risk using QRISK3-2017.

Usage

```
QRISK3_2017(
  data,
  patid,
  gender,
  age,
  atrial_fibrillation,
  atypical_antipsy,
  regular_steroid_tablets,
  erectile_disfunction,
  migraine,
  rheumatoid_arthritis,
  chronic_kidney_disease,
  severe_mental_illness,
  systemic_lupus_erythematosis,
  blood_pressure_treatment,
  diabetes1,
  diabetes2,
  weight,
  height,
  ethinicity,
  heart_attack_relative,
  cholesterol_HDL_ratio,
  systolic_blood_pressure,
  std_systolic_blood_pressure,
  smoke,
  townsend
)
```

Arguments

data	Specify your data.
patid	Specify the patient identifier.
gender	1: women 0: men.
age	Specify the age of the patient in year (e.g. 64 years-old)
atrial_fibrillation	Atrial fibrillation? (0: No, 1:Yes)

atypical_antipsy
 On atypical antipsychotic medication? (0: No, 1:Yes)

regular_steroid_tablets
 On regular steroid tablets? (0: No, 1:Yes)

erectile_disfunction
 A diagnosis of or treatment for erectile dysfunction? (0: No, 1:Yes)

migraine Do patients have migraines? (0: No, 1:Yes)

rheumatoid_arthritis
 Rheumatoid arthritis? (0: No, 1:Yes)

chronic_kidney_disease
 Chronic kidney disease (stage 3, 4 or 5)? (0: No, 1:Yes)

severe_mental_illness
 Severe mental illness? (0: No, 1:Yes)

systemic_lupus_erythematosis
 Systemic lupus erythematosis (SLE)? (0: No, 1:Yes)

blood_pressure_treatment
 On blood pressure treatment? (0: No, 1:Yes)

diabetes1 Diabetes status: type 1? (0: No, 1:Yes)

diabetes2 Diabetes status: type 2? (0: No, 1:Yes)

weight Weight of patients (kg)

height Height of patients (cm)

ethinicity Ethnic group must be coded as the same as QRISK3

1 White or not stated
 2 Indian
 3 Pakistani
 4 Bangladeshi
 5 Other Asian
 6 Black Caribbean
 7 Black African
 8 Chinese
 9 Other ethnic group

heart_attack_relative
 Angina or heart attack in a 1st degree relative < 60? (0: No, 1:Yes)

cholesterol_HDL_ratio
 Cholesterol/HDL ratio? (range from 1 to 11, e.g. 4)

systolic_blood_pressure
 Systolic blood pressure (mmHg, e.g. 180 mmHg)

std_systolic_blood_pressure
 Standard deviation of at least two most recent systolic blood pressure readings (mmHg)

smoke Smoke status must be coded as the same as QRISK3

1 non-smoker
 2 ex-smoker
 3 light smoker (less than 10)
 4 moderate smoker (10 to 19)
 5 heavy smoker (20 or over)

townsend Townsend deprivation scores

Value

Return a dataset with three columns: patient identifier, caculated QRISK3 score, caculated QRISK3 score with only 1 digit

Examples

```

data(QRISK3_2019_test)
test_all <- QRISK3_2019_test

test_all_rst <- QRISK3_2017(data=test_all, patid="ID", gender="gender", age="age",
atrial_fibrillation="b_AF", atypical_antipsy="b_atypicalantipsy",
regular_steroid_tablets="b_corticosteroids", erectile_disfunction="b_impotence2",
migraine="b_migraine", rheumatoid_arthritis="b_ra",
chronic_kidney_disease="b_renal", severe_mental_illness="b_semi",
systemic_lupus_erythematosis="b_sle",
blood_pressure_treatment="b_treatedhyp", diabetes1="b_type1",
diabetes2="b_type2", weight="weight", height="height",
ethinicity="ethrisk", heart_attack_relative="fh_cvd",
cholesterol_HDL_ratio="rati", systolic_blood_pressure="sbp",
std_systolic_blood_pressure="sbps5", smoke="smoke_cat", townsend="town")

test_all_rst$"QRISK_C_algorithm_score" <- test_all$"QRISK_C_algorithm_score"
test_all_rst$"diff" <- test_all_rst$"QRISK3_2017_1digit" - test_all_rst$"QRISK_C_algorithm_score"
print(test_all_rst$"diff")
print(identical(test_all_rst$"QRISK3_2017_1digit", test_all_rst$"QRISK_C_algorithm_score"))

```

QRISK3_2017_test *Test data for QRISK3 2017 algorithm - 2017 data*

Description

Data from QRISK3 original algorithm (C code) in 2017. The aim is to compare whether this package calculates the same score as the original algorithm. "QRISK_C_algorithm_score" in dataset is the score calculated using original algorithm in 2017. It should give the same score as this package.

Usage

```
data(QRISK3_2017_test)
```

Format

An object of class `data.frame` with 48 rows and 27 columns.

Examples

```
data(QRISK3_2017_test)
str(QRISK3_2017_test)
```

QRISK3_2019_test *Test data for QRISK3 2017 algorithm - 2019 data*

Description

Data from QRISK3 original algorithm (C code) in 2019. The aim is to compare whether this package calculates the same score as the original algorithm. "QRISK_C_algorithm_score" in dataset is the score calculated using original algorithm in 2019. It should give the same score as this package. This data was similar to QRISK3_2017_test except that several test values have been changed.

Usage

```
data(QRISK3_2019_test)
```

Format

An object of class `data.frame` with 49 rows and 27 columns.

Examples

```
data(QRISK3_2019_test)
str(QRISK3_2019_test)
```

Index

- * **QRISK3_2017**

- QRISK3_2017, [2](#)

- * **datasets**

- QRISK3_2017_test, [4](#)

- QRISK3_2019_test, [5](#)

- QRISK3_2017, [2](#)

- QRISK3_2017_test, [4](#)

- QRISK3_2019_test, [5](#)