

Package ‘RCCPCA’

January 20, 2025

Type Package

Title ``Retained Component Criterion for Principal Component Analysis''

Version 0.1.0

Date 2021-10-01

Author Fayed Alshammri

Maintainer Dr. Fayed Alshammri <fayed333@hotmail.com>

Description The RCC_PCA criterion is a tool to determine the optimal number of components to retain in PCA; See Alshammri (2021).

License GPL-2

Depends stats, graphics

Encoding UTF-8

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2021-10-05 08:10:10 UTC

Contents

| | |
|-------------------|---|
| RCC_PCA | 1 |
| Index | 3 |

RCC_PCA

Retained Component Criterion for Principal Component Analysis

Description

The RCC_PCA criterion is a new tool to determine the optimal number of components (i.e. PCs) to retain for Principal Component Analysis (PCA). This criterion balances between the following two desires, reducing the dimension of the data and increasing the accuracy of the final results of PCA; See Alshammri (2021).

Usage

```
RCC_PCA(x)
```

Arguments

- x a N-by-m data matrix, where the rows are "N" observations, and the columns are "m" variables

Value

The values of RCC criterion

Author(s)

Fayed Alshammri

References

Alshammri, F. (2021). Retained component criterion for optimizing principal component analysis. Manuscript submitted for publication.

Examples

```
##The data matrix x is the scaled first four variables of "iris data" with m=4 and N=150.  
x=scale(iris[,1:4])  
  
##calculate and plot the RCC_PCA values of x after applying PCA.  
myresults=RCC_PCA(x)  
  
##lists the values of RCC criterion  
myresults
```

Index

RCC_PCA, [1](#)