

Package ‘hakaiApi’

May 28, 2025

Title Authenticated HTTP Request Client for the 'Hakai' API

Version 1.0.3

Description Initializes a class that obtains API credentials and provides a method to use those credentials to make GET requests to the 'Hakai' API server. Usage instructions are documented at <https://hakaiinstitute.github.io/hakai-api/>.

License MIT + file LICENSE

URL <https://github.com/HakaiInstitute/hakai-api-client-r>

BugReports <https://github.com/HakaiInstitute/hakai-api-client-r/issues>

Depends R (>= 4.2.0)

Imports dplyr, httr2, R6, readr, tibble

Suggests knitr, markdown, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Encoding UTF-8

Language en-CA

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation no

Author Sam Albers [aut, cre],
Taylor Denouden [aut],
Brett Johnson [aut],
Nate Rosenstock [ctb],
Chris Davis [ctb],
Hakai Institute [cph]

Maintainer Sam Albers <sam.albers@hakai.org>

Repository CRAN

Date/Publication 2025-05-27 23:10:05 UTC

Contents

Client	2
Index	6

Client	<i>The Hakai API Client Class</i>
--------	-----------------------------------

Description

Class to use to make authenticated API requests for Hakai data

Public fields

`api_root` The `api_root` you are logged in to

Methods

Public methods:

- `Client$new()`
- `Client$get()`
- `Client$post()`
- `Client$put()`
- `Client$patch()`
- `Client$remove_credentials()`
- `Client$clone()`

Method `new()`: Log into Google to gain credential access to the API

Usage:

```
Client$new(
  api_root = "https://hecate.hakai.org/api",
  login_page = "https://hecate.hakai.org/api-client-login"
)
```

Arguments:

`api_root` Optional API base url to fetch data. Defaults to "https://hecate.hakai.org/api"
`login_page` Optional API login page url to display to user. Defaults to "https://hecate.hakai.org/api-client-login"

Returns: A client instance

Examples:

```
try(
  client <- Client$new()
)
```

Method `get()`: Send a GET request to the API

Usage:

```
Client$get(endpoint_url, col_types = NULL)
```

Arguments:

`endpoint_url` The full API url to fetch data from

`col_types` a readr type specification

Returns: A dataframe of the requested data

Examples:

```
try(client$get("https://hecate.hakai.org/api/aco/views/projects"))
```

Method `post()`: Send a POST request to the API

Usage:

```
Client$post(endpoint_url, rec_data)
```

Arguments:

`endpoint_url` The full API url to fetch data from

`rec_data` dataframe, list, or other R data structure to send as part of the post request payload

Returns: post request response status code and description

Method `put()`: Send a PUT request to the API

Usage:

```
Client$put(endpoint_url, rec_data)
```

Arguments:

`endpoint_url` The full API url to fetch data from

`rec_data` dataframe, list, or other R data structure to send as part of the post request payload

Returns: PUT request response status code and description

Method `patch()`: Send a PATCH request to the API

Usage:

```
Client$patch(endpoint_url, rec_data)
```

Arguments:

`endpoint_url` The full API url to fetch data from

`rec_data` dataframe, list, or other R data structure to send as part of the post request payload

Returns: PATCH request response status code and description

Method `remove_credentials()`: Remove your cached login credentials to logout of the client

Usage:

```
Client$remove_credentials()
```

Examples:

```
try(  
  client$remove_credentials()  
)
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Client$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## Not run:
# Initialize a new client
try(
  client <- Client$new()
)

# Follow authorization prompts to log in

# Retrieve some data. See <https://hakaiinstitute.github.io/hakai-api/> for options.
try(
  url <- paste0(client$api_root, "/aco/views/projects?project_year=2020&fields=project_name")
)

try(
  projects_2020 <- client$get(url)
)

try(
  print(projects_2020)
)
# # A tibble: 20 x 1
#   project_name
#   <chr>
# 1 Fountain FN
# 2 Haig Glacier
# 3 Fraser River - Chimney Creek West William Canyon
# 4 Cruickshank WS
# ...

## End(Not run)

## -----
## Method `Client$new`
## -----

try(
  client <- Client$new()
)

## -----
## Method `Client$get`
## -----

try(client$get("https://hecate.hakai.org/api/aco/views/projects"))

## -----
## Method `Client$remove_credentials`
## -----

try(
  client$remove_credentials()
```

)

Index

Client, [2](#)