

# Package ‘mod09nrt’

October 13, 2022

**Type** Package

**Title** Extraction of Bands from MODIS Surface Reflectance Product MOD09  
NRT

**Version** 0.14

**Author** Rishabh Gupta <rishabh.uk@gmail.com>, Nicholas J. Matzke, Dept. of Integrative Biology, U.C. Berkeley

**Maintainer** Rishabh Gupta <rishabh.uk@gmail.com>

**Description** Package for processing downloaded MODIS Surface reflectance Product HDF files. Specifically, MOD09 surface reflectance product files, and the associated MOD03 geolocation files (for MODIS-TERRA). The package will be most effective if the user installs MRTSwath (MODIS Reprojection Tool for swath products; <[https://lpdaac.usgs.gov/tools/modis\\_reprojection\\_tool\\_swath](https://lpdaac.usgs.gov/tools/modis_reprojection_tool_swath)>, and adds the directory with the MRTSwath executable to the default R PATH by editing ~/.Rprofile.

**SystemRequirements** MRTSwath

**License** GPL (>= 2)

**LazyData** TRUE

**RoxygenNote** 5.0.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2016-07-24 13:55:50

## R topics documented:

adf . . . . .	2
check_for_matching_geolocation_files_mod09nrt . . . . .	2
extract_fn_from_path . . . . .	4
run_swath2grid_mod09nrt . . . . .	5
slashslash . . . . .	7
write_MRTSwath_param_file_mod09nrt . . . . .	8

<b>Index</b>	<b>10</b>
--------------	-----------

adf	<i>Convert to data.frame, without factors</i>
-----	---

## Description

Shortcut for: `as.data.frame(x, row.names=NULL, stringsAsFactors=FALSE)`

## Usage

```
adf(x)
```

## Arguments

x	matrix or other object transformable to data.frame
---	--

## Details

This function is useful for dealing with errors due to automatic conversion of some columns to factors. Another solution may be to prepend `options(stringsAsFactors = FALSE)` at the start of one's script, to turn off all default stringsAsFactors silliness.

## Value

`data.frame`

## Author(s)

Nicholas J. Matzke <[matzke@berkeley.edu](mailto:matzke@berkeley.edu)>

## Examples

```
x = matrix(c(1,2,3,4,5,6), nrow=3, ncol=2)
adf(x)
```

check_for_matching_geolocation_files_mod09nrt	
---	--

	<i>Checks that every MODIS surface reflectance project HDF has a matching MOD03 file</i>
--	--

## Description

Each MOD09 surface reflectance product file requires a corresponding MOD03 geolocation file to be successfully processed with the MRTSwath tool.

**Usage**

```
check_for_matching_geolocation_files_mod09nrt(moddir = getwd(),  
  modtxt = "MOD09", geoloctxt = "MOD03", return_geoloc = FALSE,  
  return_product = FALSE)
```

**Arguments**

moddir	the string describing the directory containing the MOD09 and MOD03 files; both must be in the same directory. Default: getwd(), which gives the present working directory.
modtxt	the text string indicating which HDF files are the MODIS surface reflectance product (or hypothetically, other product). Default: MOD09 (MODIS surface reflectance product)
geoloctxt	the text string indicating which HDF files are the MODIS geolocation files (or hypothetically, another set of files). Default: MOD03
return_geoloc	if TRUE, return the list of unmatched geolocation files (e.g. MOD03 )
return_product	if TRUE, return the list of unmatched product files (e.g. MOD09)

**Details**

MRTSwath is the MRT (MODIS Reprojection Tool) for the MODIS

E.g. this surface reflectance file:

MOD09.A2016204.0500.005.2016204062219.NRT.hdf

...goes with this corresponding geolocation file:

MOD03.A2016204.0500.005.2016204060250.NRT.hdf

...which is a large file (~30 MB) containing detailed information on the position, tilt, etc. of the MODIS satellite. MRTSwath tool needs one of each, however.

**Value**

data.frame of matching files; or a list of non-matching files, if `return_geoloc` or `return_product` are TRUE.

**Author(s)**

Rishabh Gupta <rishabh.uk@gmail.com>

**Examples**

```
# Check your working directory  
moddir = getwd()  
  
# Here are some example MODIS files in mod09nrt/extdata/  
# Code excluded from CRAN check because it depends on modiscdata  
## Not run:  
library(devtools)  
library(modiscdata)
```

```

moddir = system.file("extdata/2002raw/", package="modiscdata")

# You need to have some e.g. MOD files in it (from the MODIS-TERRA platform)
list.files(path=moddir, pattern="MOD")
list.files(path=moddir, pattern="MOD")

# Check for matches (for MODIS-TERRA platform)
check_for_matching_geolocation_files_mod09nrt(moddir=moddir, modtxt="MOD09", geoloctxt="MOD03",
return_geoloc=FALSE, return_product=FALSE)

## End(Not run)

```

**extract\_fn\_from\_path** *Get the filename from a path*

## Description

The filename is split on slashes, and the last item is taken; this should be just the filename.

## Usage

```
extract_fn_from_path(fn_with_path)
```

## Arguments

**fn\_with\_path** The filename, with partial or full path

## Value

**fn** The extracted filename

## Author(s)

Nicholas J. Matzke <matzke@berkeley.edu>

## See Also

[strsplit](#)

## Examples

```

fn_with_path = "/Library/Frameworks/R.framework/Versions/2.15/Resources/library/modiscloud/extdata
/2002raw/MYD35_L2.A2002185.1910.005.2007206043609.hdf"
extract_fn_from_path(fn_with_path)

```

---

**run\_swath2grid\_mod09nrt**

*Run MRTSwath swath2grid tool*

---

## Description

MRTSwath is the "MODIS Reprojection Tool for swath products". See: [https://lpdaac.usgs.gov/tools/modis\\_reprojection\\_tool\\_swath](https://lpdaac.usgs.gov/tools/modis_reprojection_tool_swath)).

## Usage

```
run_swath2grid_mod09nrt(mrtpath = "swath2grid", prmfn = "tmpMRTparams.prm",
  tifsdir, modfn, geoloc_fn, ul_lon, ul_lat, lr_lon, lr_lat)
```

## Arguments

mrtpath	This is the path to the MRTSwath executable <code>swath2grid</code> . If your <code>~/.Rprofile</code> file has the location of <code>swath2grid</code> in the PATH, then you can just use <code>mrtpath="swath2grid"</code> . Otherwise, the user must provide the full path to <code>swath2grid</code> .
prmfn	The name of the parameter/control file which will be the input to MRTSwath's <code>swath2grid</code> function.
tifsdir	The directory to save the output TIF files in
modfn	The filename of the MODIS data
geoloc_fn	The filename of the corresponding geolocation file (annoyingly, this is a much larger file than the data file!)
ul_lon	Upper left (ul) longitude (x-coordinate) for subsetting
ul_lat	Upper left (ul) latitude (y-coordinate) for subsetting
lr_lon	Lower right (lr) longitude (x-coordinate) for subsetting
lr_lat	Lower right (lr) latitude (y-coordinate) for subsetting

## Details

If you want this function to use MRTSwath tool successfully, you should add the directory with the MRTSwath executable to the default R PATH by editing `~/.Rprofile`.

## Value

`cmdstr` The string giving the system command that ran `swath2grid`

## Author(s)

Nicholas J. Matzke <[matzke@berkeley.edu](mailto:matzke@berkeley.edu)>

**See Also**

[write\\_MRTSwath\\_param\\_file\\_mod09nrt](#)

[http://landweb.nascom.nasa.gov/cgi-bin/QA\\_WWW/newPage.cgi?fileName=hdf\\_filename](http://landweb.nascom.nasa.gov/cgi-bin/QA_WWW/newPage.cgi?fileName=hdf_filename)  
@cite NASA2001

**Examples**

```
#####
# Run MRTSwath tool "swath2grid"
#####

# Source MODIS files (both data and geolocation)
# Code excluded from CRAN check because it depends on modiscdata
## Not run:
library(devtools)
library(modiscdata)
moddir = system.file("extdata/2002raw/", package="modiscdata")

# Get the matching data/geolocation file pairs
fns_df = check_for_matching_geolocation_files(moddir, modtxt="MOD09", geoloctxt="MOD03")
fns_df

# Resulting TIF files go in this directory
tifsdir = getwd()

# Box to subset
ul_lat = 13
ul_lon = -87
lr_lat = 8
lr_lon = -82

for (i in 1:nrow(fns_df))
{
  prmf = write_MRTSwath_param_file_mod09nrt(prmf="tmpMRTparams.prm", tifsdir=tifsdir,
  modfn=fns_df$mod09_fns[i], geoloc_fn=fns_df$mod03_fns[i], ul_lon=ul_lon, ul_lat=ul_lat,
  lr_lon=lr_lon, lr_lat=lr_lat)
  print(scan(file=prmf, what="character", sep="\n"))

  run_swath2grid_mod09nrt(mrtpath="swath2grid", prmf="tmpMRTparams.prm", tifsdir=tifsdir,
  modfn=fns_df$mod309_fns[i], geoloc_fn=fns_df$mod03_fns[i], ul_lon=ul_lon, ul_lat=ul_lat,
  lr_lon=lr_lon, lr_lat=lr_lat)
}

list.files(tifsdir, pattern=".tif", full.names=TRUE)

## End(Not run)
```

---

**slashslash***Remove double slash (slash a slash)*

---

## Description

Shortcut for: gsub(pattern="//", replacement="/", x=tmpstr)

## Usage

```
slashslash(tmpstr)
```

## Arguments

tmpstr	a path that you want to remove double slashes from
--------	--

## Details

This function is useful for removing double slashes that can appear in full pathnames due to inconsistencies in trailing slashes in working directories etc.

## Value

outstr a string of the fixed path

## Author(s)

Nicholas J. Matzke <matzke@berkeley.edu>

## See Also

[gsub](#)

## Examples

```
tmpstr = "/Library/Frameworks/R.framework/Versions/2.15/Resources/library/modiscloud/extdata/
2002raw//MYD03.A2002185.0645.005.2009192031332.hdf"

outstr = slashslash(tmpstr)
outstr
```

**write\_MRTSwath\_param\_file\_mod09nrt***Write a parameter control file for MRTSwath***Description**

MRTSwath is the "MODIS Reprojection Tool for swath products". See: [https://lpdaac.usgs.gov/tools/modis\\_reprojection\\_tool\\_swath](https://lpdaac.usgs.gov/tools/modis_reprojection_tool_swath)).

**Usage**

```
write_MRTSwath_param_file_mod09nrt(prmfn = "tmpMRTparams.prm", tifsdir, modfn,
                                    geoloc_fn, ul_lon, ul_lat, lr_lon, lr_lat)
```

**Arguments**

<code>prmfn</code>	The name of the parameter/control file which will be the input to MRTSwath's <code>swath2grid</code> function.
<code>tifsdir</code>	The directory to save the output TIF files in
<code>modfn</code>	The filename of the MODIS data
<code>geoloc_fn</code>	The filename of the corresponding geolocation file (annoyingly, this is a much larger file than the data file!)
<code>ul_lon</code>	Upper left (ul) longitude (x-coordinate) for subsetting
<code>ul_lat</code>	Upper left (ul) latitude (y-coordinate) for subsetting
<code>lr_lon</code>	Lower right (lr) longitude (x-coordinate) for subsetting
<code>lr_lat</code>	Lower right (lr) latitude (y-coordinate) for subsetting

**Details**

If you want this function to use MRTSwath tool successfully, you should add the directory with the MRTSwath executable to the default R PATH by editing `~/.Rprofile`.

This function hard-codes these options into the parameter file:

- \* all the bands are extracted
- \* the output file is a GeoTIFF
- \* the output projection is Geographic (plain unprojected Latitude/Longitude)
- \* the resampling is Nearest Neighbor (NN), which of course is the only one which makes sense when the pixels encode bytes that encode bits that encode discrete classification results, 0/1 error flags, etc.

MRTswath can do many other projections and output formats; users can modify this function to run those options.

**Value**

`prmfn` The name of the temporary parameter file

**Author(s)**

Rishabh Gupta <rishabh.uk@gmail.com>

**See Also**

[run\\_swath2grid\\_mod09nrt](#)  
[@cite NASA2001](http://landweb.nascom.nasa.gov/cgi-bin/QA_WWW/newPage.cgi?fileName=hdf_filename)

**Examples**

```
# Source MODIS files (both data and geolocation)
# Code excluded from CRAN check because it depends on modiscdata
## Not run:
library(devtools)
library(modiscdata)
moddir = system.file("extdata/2002raw/", package="modiscdata")

# Get the matching data/geolocation file pairs
fns_df = check_for_matching_geolocation_files_mod09nrt(moddir, modtxt="MOD09", geoloctxt="MOD03")
fns_df

# Resulting TIF files go in this directory
tifsdir = getwd()

# Box to subset
ul_lat = 13
ul_lon = -87
lr_lat = 8
lr_lon = -82

for (i in 1:nrow(fns_df))
{
  prmf = write_MRTSwath_param_file_mod09nrt(prmf="tmpMRTparams.prm", tifsdir=tifsdir,
  modfn=fns_df$mod09_fns[i], geoloc_fn=fns_df$mod03_fns[i], ul_lon=ul_lon, ul_lat=ul_lat,
  lr_lon=lr_lon, lr_lat=lr_lat)
  print(scan(file=prmf, what="character", sep="\n"))

}

## End(Not run)
```

# Index

adf, 2  
check\_for\_matching\_geolocation\_files\_mod09nrt,  
    2  
extract\_fn\_from\_path, 4  
gsub, 7  
run\_swath2grid\_mod09nrt, 5, 9  
slashslash, 7  
strsplit, 4  
write\_MRTSwath\_param\_file\_mod09nrt, 6,  
    8