

Package ‘roughsf’

October 14, 2022

Title Visualize Spatial Data using 'roughjs'

Version 1.0.0

Description Draw maps using the 'javascript' library 'roughjs'. This allows to draw sketchy, hand-drawn-like maps.

URL <https://github.com/schochastics/roughsf>

BugReports <https://github.com/schochastics/roughsf/issues>

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.1

Imports htmlwidgets, jsonlite, sf

Suggests pagedown

NeedsCompilation no

Author David Schoch [aut, cre] (<<https://orcid.org/0000-0003-2952-4812>>)

Maintainer David Schoch <david@schochastics.net>

Repository CRAN

Date/Publication 2022-10-04 10:20:02 UTC

R topics documented:

roughsf	2
save_roughsf	4

Index

5

roughsf*Create a rough map*

Description

plot a sf map using rough.js

Usage

```
roughsf(
  layers,
  roughness = 1,
  bowing = 1,
  simplification = 1,
  font = "30px Arial",
  title = NULL,
  title_font = "30px Arial",
  caption = NULL,
  caption_font = "30px Arial",
  width = NULL,
  height = NULL,
  elementId = NULL,
  chunk_name = "canvas"
)
```

Arguments

<code>layers</code>	an sf object or a list of sf object. each object should only contain one type of geometry.
<code>roughness</code>	numeric vector for roughness of lines
<code>bowing</code>	numeric vector for bowing of lines
<code>simplification</code>	simplify drawings (remove points from objects)
<code>font</code>	font size and font family for labels
<code>title</code>	optional title of the map
<code>title_font</code>	font size and font family for title
<code>caption</code>	optional caption of the map
<code>caption_font</code>	font size and font family for caption
<code>width</code>	width
<code>height</code>	height
<code>elementId</code>	DOM id
<code>chunk_name</code>	markdown specific

Details

The following attributes are supported for POLYGONS:

- *fill* fill color
- *color* stroke color
- *stroke* stroke size
- *fillstyle* one of "hachure", "solid", "zigzag", "cross-hatch", "dots", "dashed", "zigzag-line"
- *fillweight* thickness of fillstyle (between 0 and 1)
- *hachureangle* angle of hachure lines
- *hachuregap* gap between two hachure lines

The following attributes are supported for LINESTRINGS:

- *color* stroke color
- *stroke* stroke size

The following attributes are supported for POINTS:

- *color* color of point
- *size* size of point
- *label* label to be added (optional)
- *label_pos* position of label relative to point: (c)enter, (n)orth, (e)ast, (s)outh, (w)east (optional)

Default values are used if one of the attributes is not found.

The result of a roughsf call can be printed to file with `save_roughsf()`

Value

htmlwidget containing the drawn network

References

More details on roughjs can be found on <https://github.com/rough-stuff/rough/wiki>

Examples

```
library(sf)
demo(nc, ask = FALSE, echo = FALSE)
nc_poly <- st_cast(nc, "POLYGON", warn = FALSE)
roughsf(nc_poly)
```

save_roughsf *Save roughsf plot to file*

Description

Save roughsf plot to file

Usage

```
save_roughsf(rsf, file, background = "white", wait = 4)
```

Arguments

rsf	result from calling the function roughsf
file	filename
background	string giving the html background color
wait	time in seconds to wait for page load

Value

No return value, called for side effect

Index

roughsf, [2](#)

save_roughsf, [4](#)